

NGM512

Shotgun Microphone



OVERVIEW

NGM512 is a professional shotgun type gooseneck microphone specifically designed for NCS flush mounts units. The gooseneck microphones offers superior off axis rejection and the frequency response is adjusted to create excellent intelligibility over the speech. The Microphones offers a wide frequency range of 50 Hz - 20 kHz, suitable for natural audio reproduction. The Gooseneck Microphone is equipped with screw type holder designed to firmly lock the base of the conference microphone to prevent various failures caused by looseness or poor contact. The LED ring at the bottom of the microphone responds according to the status of the discussion unit

TECHNICAL SPECIFICATIONS

Capsule Type:	Condenser
Polar Pattern:	Super Cardioid
Frequency Response:	50Hz-20KHz
Sensitivity:	-20dB+/-3dB(0dB=1V/Pa,f=1KHz)
SPL:	110dB(THD<5%, f=1KHz)><5%, f=1KHz)
S/N Ratio(A weighted):	>100dBA(THD<5%, f=1KHz)><1%, f=1KHz)
Distortion:	<0.1%
Power Supply:	5V DC
Output Connector:	XLRM
Dimensions:	285(L)
Weight:	180g

KEY FEATURES

- Screw Type detachable Shotgun Microphone for NCS Flush Mount discussion units
- Superior off axis rejection with super – cardioid pick up pattern
- Wide frequency response for natural audio reproduction
- In built LED ring indicator to indicate On/Off status
- Superior Brass Body with black matte finish