

KYRO KUSB2

USB 2channel

KYRO KUSB2 USB Sound Card** is designed for integrating USB-type signals into the system. This card is highly versatile, supporting applications such as recording, video conferencing, and test signal access. It offers a level fader range of -60dB to 0dB and provides a convenient connection status display. Equipped with a Type 2 USB interface, it ensures easy connectivity with PCs or other USB-compatible devices. s



KEY FEATURES

- . THE USB SOUND CARD IS USED FOR SYSTEM ACCESS TO USB-TYPE SIGNALS AND CAN BE USED FOR RECORDING, VIDEO CONFERENCING, AND TEST SIGNAL INPUT.
- . IT HAS A LEVEL ADJUSTMENT RANGE OF -60~0DB WITH SUPPORT FOR CONNECTION STATUS DISPLAY.
- . THE TWO USB INTERFACES FACILITATE CONNECTION WITH PCS OR OTHER USB-TYPE DEVICES.
- .EQUIPPED WITH A QUICK INSTALLATION INTERFACE.
- .CONTROL AND CONFIGURATION CAN BE DONE THROUGH SOFTWARE.

TECHNICAL SPECIFICATIONS

SAMPLING RATE	48KHZ	QUANTIZATION BIT DEPTH	24-BIT
USB-C LINE	2X2	HOT-SWAPPABLE	SUPPORT