

KYRO DC22

OLED network control panel



This Dante-enabled 2-channel audio interface features balanced XLR microphone/line inputs and outputs with PoE power support for easy installation. It provides selectable input gain, +48V phantom power, and high-quality low-noise audio performance, making it ideal for professional AV, conferencing, and fixed installation systems.

KEY FEATURES

- . 2 balanced XLR microphone/line inputs.
- . 2 balanced XLR line outputs.
- . Power over Ethernet that complies with the 802.3af standard requires the use of standard-compliant Ethernet.
- . Power supply network switch.
- . Three input gain levels for commonly used line levels, phantom power and dynamic microphones.
- . Each channel has +48V phantom power, which can be used for almost all commonly used in fixed installation systems.
- . Type of phantom power microphone powered.

TECHNICAL SPECIFICATIONS

Analog input channels	2	Noise floor	-97dBu
Analog output channels	2	Input impedance	20 kΩ
Dante Type	Ultimo 2	Output impedance	100Ω
Analog maximum gain	20dB	Channel isolation	100dB @ 1kHz
Frequency response	±0.2dB (20~20kHz)	Power supply	PoE
Maximum level	+8dBu, balanced	Size	W110×H110×D50 mm
THD+N	<0.002% @ 4dBu		